

Compare Products	
Code	70970
Model	XJ37
	
Note	<p style="text-align: center;">DRIVE DIVER REMOTE INFORMATION VIEW</p> <p style="text-align: center;">Notes : - The runtime varies trimming the speed knob - Speed varies with diver's equipment and trim/position - Parameters for continuous running</p>
Dimensions	
Use	TECH / COMMERCIALLONG RANGE / CAVE
Length	mm 790 (inch 31,1)
Width	mm 436 (inch 17,2)
Height	mm 340 (inch 13,4)
Body diameter	mm 197 (inch 7,8)
Weight without battery	kg 14 (lb 30,9)
Weight with battery	kg 20 (lb 44,1)
Material type	Aluminum body
Performance	
Max static thrust	N 330 (lb 74,2)
Top speed	mt/min 85 (ft/min 278)
Run time at max speed/drag	min
Maximum operational depth	mt 200 (ft 656)
Test depth	mt 300 (ft 984)
Buoyancy/ trim	Neutral Trim and Buoyancy
In-water usage temperature	°C -5/+35 (°F +23/+95)

Runtime-range

SPEED MT/MIN	BURNTIME - MIN	RANGE KM (nm)
FULL TRIGGER	85	5,9 (2,7)
60-2KNOTS	120	7,2 (3,8)
45-CRUISE	180	8,1 (4,3)
30	270	

- Max speed is delivered with fully charged battery
 - Diver : 70kg weight, 170cm high - drysuit - double 12 tanks - horizontal trim
 - Conditions : fresh water - no flow

Battery type

Battery type	LI-ion
Nominal Voltage	Volt 25,2
Nominal Capacity	Wh 940
Cells	
Maximum recharging time	h 8
Charger power supply	90/240 - 50/60 Hz

Features

DRIVE	●
Fastening device	●
Main Switch	●
Speed Adjustment	●
Battery Gauge	●
By-pass System	●
Made Salt Resistant	●
Battery and Charger Design and Quality	●
NBS - Easy Trim and Buoyancy	●
Easy Trim	●
Easy Inspect	●
Sealed Motor Compartment	●
Proplock Propeller	●
Motor Protection	●
Battery Protection System	●
N-Handle	
Rainbow	
Certifications	●
Modularity	●

Features legend:

● : standard

○ : optional

○ : not available